



GENERAL NOTES:

1. NEMA 1 ENCLOSURE, 18" x 18" x 6".
2. SHORT CIRCUIT CURRENT RATING:
5,000 AMPS RMS SYMMETRICAL.

NOTES:

1. 208 VAC, 3 ϕ , 60 HZ SERVICE.
USE COPPER WIRE, 75° C INSULATION.
FIELD TO INSTALL DISCONNECTING MEANS
AND FUSE/BREAKER PROTECTION.
2. PCS IS FIELD SUPPLIED.
CONTACT CLOSURE STARTS PUMP.

LEGEND:

- F = FUSE
- G = GROUND
- HOAS = HAND-OFF-AUTO SWITCH
- HP = HORSEPOWER
- L = LINE
- M = MOTOR
- MS = MOTOR STARTER
- OL = OVERLOAD
- PCS = PUMP CONTROL SWITCH
- RL = RUN LIGHT
- T = TRANSFORMER
- TTS = TRIPLEX TRANSFER SWITCH

INTERNAL CONDUCTOR

EXTERNAL CONDUCTOR

○ ELECTRICAL CONNECTION

Revisions:

-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-
-	-	-

bfs INDUSTRIES, LLC
BUTNER, NORTH CAROLINA

DESCRIPTION *3LPR24-1/2 TRIPLEX FEED-PAC*

S.O.#

JOB

CUSTOMER

THIS DRAWING IS THE PROPERTY OF BFS INDUSTRIES, LLC, AND IS SUBJECT TO CHANGE WITHOUT NOTICE. THE INFORMATION CONTAINED HEREIN IS TO BE USED ONLY FOR THE JOB INDICATED, AND IS NOT TO BE COPIED, TRANSMITTED OR USED IN ANY WAY DETRIMENTAL TO THE COMPANY.

Scale: <i>NONE</i>	Date	Drawing no	Rev.
Drawn		<i>19995B-SC</i>	<i>0</i>
Appvd: <i>J. Samborsky</i>			